


MC319Z RFID Mobile Computer

Integrator Guide



**MC319Z RFID Mobile Computer
Integrator Guide**

72E-146158-03

Revision A

March 2015

© 2015 Symbol Technologies, Inc.

No part of this publication may be reproduced or used in any form, or by any electrical or mechanical means, without permission in writing from Zebra. This includes electronic or mechanical means, such as photocopying, recording, or information storage and retrieval systems. The material in this manual is subject to change without notice.

The software is provided strictly on an “as is” basis. All software, including firmware, furnished to the user is on a licensed basis. Zebra grants to the user a non-transferable and non-exclusive license to use each software or firmware program delivered hereunder (licensed program). Except as noted below, such license may not be assigned, sublicensed, or otherwise transferred by the user without prior written consent of Zebra. No right to copy a licensed program in whole or in part is granted, except as permitted under copyright law. The user shall not modify, merge, or incorporate any form or portion of a licensed program with other program material, create a derivative work from a licensed program, or use a licensed program in a network without written permission from Zebra. The user agrees to maintain Zebra’s copyright notice on the licensed programs delivered hereunder, and to include the same on any authorized copies it makes, in whole or in part. The user agrees not to decompile, disassemble, decode, or reverse engineer any licensed program delivered to the user or any portion thereof.

Zebra reserves the right to make changes to any software or product to improve reliability, function, or design.

Zebra does not assume any product liability arising out of, or in connection with, the application or use of any product, circuit, or application described herein.

No license is granted, either expressly or by implication, estoppel, or otherwise under any Zebra Technologies Corporation, intellectual property rights. An implied license only exists for equipment, circuits, and subsystems contained in Zebra products.

Zebra and the Zebra head graphic are registered trademarks of ZIH Corp. The Symbol logo is a registered trademark of Symbol Technologies, Inc., a Zebra Technologies company.

Zebra Technologies Corporation
Lincolnshire IL, U.S.A.
<http://www.zebra.com>

Warranty

For the complete Zebra hardware product warranty statement, go to:
<http://www.zebra.com/warranty>.

Revision History

Changes to the original manual are listed below:

Change	Date	Description
-01 Rev A	2/2011	Initial release
-02 Rev A	01/2014	Add battery configuration. Update web addresses.
-03 Rev A	3/2015	Zebra Rebranding

Table of Contents

Warranty	ii
Revision History	iii

Table of Contents

About This Guide

Introduction	ix
Configurations.....	ix
Chapter Descriptions	x
Notational Conventions.....	x
Related Documents and Software	xi
Service Information.....	xi

Chapter 1: Getting Started

Introduction	1-1
RFID Technology Overview	1-1
RFID Components	1-2
MC319Z RFID Mobile Computer	1-3
MC319Z RFID Mobile Computer Parts	1-4
MC319Z RFID Mobile Computer LEDs	1-5
Reading Tags	1-5

Chapter 2: Updating the Mobile Computer

Introduction	2-1
Updating the Device Image	2-1
Downloading an Update Loader Package	2-1
Updating Images via ActiveSync	2-1
Updating Images via AirBEAM	2-2
Updating the RFID Firmware	2-2

Chapter 3: MobileRFID Functionality

Introduction	3-1
MobileRFID Icons	3-2
MobileRFID Menu	3-3
Configure Region	3-4
Configure RFID	3-7
Version Information	3-8
Run/Stop RFID	3-9
Battery Configuration	3-10

Chapter 4: RFID Sample Application

Introduction	4-1
Launching the RFID Sample Application	4-2
Connection	4-3
Capabilities	4-4
Configuration Menu Options	4-5
Tag Storage Settings	4-5
Antenna	4-6
RF Mode	4-7
Singulation	4-8
Power On/Off Radio	4-9
Reset to Factory Default	4-9
Operations Menu Options	4-10
Antenna Info	4-10
Filter	4-11
Access	4-14
Triggers	4-18
Management Menu Options	4-24
Help Menu	4-24
Exit	4-24

Chapter 5: Tag Locator

Introduction	5-1
Using Tag Locator	5-2
Locating Tags Using a .csv File	5-3

Chapter 6: Troubleshooting

Introduction	6-1
Troubleshooting	6-1

Appendix A: Technical Specifications

Technical Specifications	A-1
--------------------------------	-----

Appendix B: RFID APIs

Index

About This Guide

Introduction

This *MC319Z RFID Integrator Guide* provides the unique set up and operating procedures for the MC319Z RFID mobile computers. This guide is intended as a supplement to the *MC3000 Integrator Guide*, p/n 72E-68900-xx. Procedures common to MC3000 products are addressed in the *MC3000 Integrator Guide*.

✓ **NOTE** Screens and windows pictured in this guide are samples and may differ from actual screens.

Configurations

All MC319Z models support the following features:

- Windows Mobile 6.5 Platform
- 256 MB RAM / 1 GB Flash
- 48-key alphanumeric keypad
- Color display
- WLAN 802.11 a/b/g radio
- Bluetooth

This guide covers the following configurations:

Configuration	Country Support	Power	Data Capture
MC319Z-GL4H24EIW	Worldwide	1 W	Laser, RFID
MC319Z-GL4H24EIE	Europe	0.5 W	Laser, RFID
MC319Z-GI4H24EIW	Worldwide	1 W	Imager, RFID
MC319Z-GI4H24EIE	Europe	0.5 W	Imager, RFID

Chapter Descriptions

Topics covered in this guide are as follows:

- [Chapter 1, Getting Started](#) provides an overview of RFID technology and components and a description of the MC319Z RFID mobile computer and features.
- [Chapter 2, Updating the Mobile Computer](#) describes how to update the device image and radio firmware.
- [Chapter 3, MobileRFID Functionality](#) includes information on configuring the RFID radio and reading tags.
- [Chapter 4, RFID Sample Application](#) provides information on the RFID sample application and how to use it to assist in custom application development.
- [Chapter 5, Tag Locator](#) provides information on the application used to detect the location of a tag.
- [Chapter 6, Troubleshooting](#) describes MC319Z RFID mobile computer troubleshooting procedures.
- [Appendix A, Technical Specifications](#) includes the technical specifications for the reader.
- [Appendix B, RFID APIs](#) provides a reference for information on supported RFID APIs.

Notational Conventions

The following conventions are used in this document:

- “Mobile computer” or “reader” refers to the MC319Z RFID mobile computer.
- *Italics* are used to highlight the following:
 - Chapters and sections in this and related documents
 - Dialog box, window, links, software names, and screen names
 - Drop-down list, columns and list box names
 - Check box and radio button names
 - Icons on a screen
- **Bold** text is used to highlight the following:
 - Dialog box, window and screen names
 - Drop-down list and list box names
 - Check box and radio button names
 - Icons on a screen
 - Key names on a keypad
 - Button names on a screen
- Bullets (•) indicate:
 - Action items
 - Lists of alternatives
 - Lists of required steps that are not necessarily sequential.
- Sequential lists (e.g., those that describe step-by-step procedures) appear as numbered lists.

Related Documents and Software

The following documents provide more information about the reader.

- *MC319Z RFID Mobile Computer Quick Start Guide*, p/n 72-146160-xx
- *MC319Z RFID Mobile Computer Regulatory Guide*, p/n 72-146159-xx
- *MC3000 Mobile Computer User Guide*, p/n 72E-68899-xx
- *MC3000 Mobile Computer Integrator Guide*, p/n 72E-68900-xx
- *Microsoft Applications for Windows Mobile 6 User Guide*, p/n 72E-108299-xx
- *Application Guide for Zebra Devices*, p/n 72E-68902-xx
- *Wireless Fusion Suite User Guide for Version 3.00*, p/n 72E-122495-xx
- *Mobility Services Platform 3.2 User's Guide*, p/n 72E-100158-xx
- *MC319Z RFID Enterprise Mobility Developer Kit*

For the latest version of this guide and all guides, go to: <http://www.zebra.com/support>.

Service Information

If you have a problem with your equipment, contact Zebra support for your region. Contact information is available at: <http://www.zebra.com/support>.

When contacting Zebra support, please have the following information available:

- Serial number of the unit
- Model number or product name
- Software type and version number

Zebra responds to calls by e-mail, telephone or fax within the time limits set forth in service agreements.

If your problem cannot be solved by Zebra support, you may need to return your equipment for servicing and will be given specific directions. Zebra is not responsible for any damages incurred during shipment if the approved shipping container is not used. Shipping the units improperly can possibly void the warranty.

If you purchased your business product from a Zebra business partner, please contact that business partner for support.

Chapter 1 Getting Started

Introduction

This chapter provides an overview of RFID technology and components, and describes the MC319Z RFID mobile computer and its features.

RFID Technology Overview

RFID (Radio Frequency Identification) is an advanced automatic identification (Auto ID) technology that uses radio frequency signals to identify *tagged* items. An RFID tag contains a circuit that can store data. This data may be pre-encoded or can be encoded in the field. The tags come in a variety of shapes and sizes.

To read a tag the mobile computer sends out radio frequency waves using its integrated antenna. This RF field powers and charges the tags, which are tuned to receive radio waves. The tags use this power to modulate the carrier signal. The reader interprets the modulated signal and converts the data to a format for computer storage. The computer application translates the data into an understandable format.



Figure 1-1 *RFID System Elements*

RFID Components

Zebra RFID solutions offer low cost, long read range, and a high read rate. These features provide real time end-to-end visibility of products and assets in the factory, distribution center, retail outlet, or other facility. The MC319Z RFID system consists of the following components:

- Silicon-based RFID tags that attach to retail products, vehicles, trailers, containers, pallets, boxes, etc.
- An integrated antenna that supports applications such as item level tracking and asset tracking.
- An embedded radio module that powers and communicates with tags for data capture and provides host connectivity for data migration.

Tags

Tags contain embedded chips that store unique information. Available in various shapes and sizes, tags, often called **transponders**, receive and respond to data requests. Tags require power to send data.

There are several categories of tags based on the protocol they support, read/write memory, and power options:

- Active RFID tags are powered by internal light-weight batteries, and also use these batteries to broadcast radio waves to the reader.
- Semi-passive RFID tags are also powered by internal light-weight batteries, but draw broadcasting power from the reader.
- Passive RFID tags are powered by a reader-generated RF field. These tags are much lighter and less expensive than active tags, and are typically applied to less expensive goods.

Antenna

Antennas transmit and receive radio frequency signals.

Radio Module

The radio module communicates with the tags and transfers the data to a host computer. It also provides features such as filtering, CRC check, and tag writing. The MC319Z RFID mobile computer supports standard RFID tags as described by EPCGlobal™ Class 1 Gen2 protocol.

MC319Z RFID Mobile Computer

The Zebra MC319Z RFID mobile computer includes an intelligent C1G2 UHF RFID reader with RFID read performance that provides real-time, seamless EPC-compliant tags processing. MC319Z RFID mobile computers are designed for indoor inventory management and asset tracking applications, and can host third-party, customer-driven embedded applications. Features include:

- ISO 18000-6C standard (EPC Class 1 Gen 2)
- Read, write, kill, lock, block write/block erase, and permalock functionality
- 48-key alphanumeric keypad
- 3" color display
- Orientation-insensitive integrated external antenna
- Laser-based bar code reader - reads 1D bar codes
- Windows® Mobile 6.5
- WLAN 802.11 a/b/g wireless connectivity
- Application-specific setup for ease of installation
- Low Level Reader Protocol (LLRP)
- Sample application and support for custom or third-party applications
- RFID API support
- Event and tag management support




Figure 1-2 MC319Z RFID Mobile Computer

The MC319Z RFID mobile computer provides a wide range of features that enable implementation of complete, high-performance, intelligent RFID solutions.

✓ **NOTE** The MC319Z RFID mobile computer supports a 2x battery only; do not use a 1x battery. The Four-Slot Cradle does not accommodate the MC319Z RFID mobile computer.

Due to component tolerances, some users may experience undesired behavior when using battery part number 55-060112-xx. If the unit turns off without proper warning messages during heavy use, use battery 55-002152-xx (p/n 82-127909-xx).

MC319Z RFID Mobile Computer Parts




Figure 1-3 MC319Z RFID Mobile Computer Parts

MC319Z RFID Mobile Computer LEDs

The mobile computer LEDs indicate charging and reader status as described in [Table 1-1](#).

Table 1-1 LED Status Indicators

LED	Indication
Charging Indicators	
Off	Mobile computer not placed correctly in the cradle; cable not connected correctly; charger is not powered.
Fast Blinking Amber	Error in charging; check placement of mobile computer.
Slow Blinking Amber	Mobile computer is charging.
Solid Amber	Charging complete. Note: When the battery is initially inserted in the mobile computer, the amber LED flashes once if the battery power is low or the battery is not fully inserted.

Reading Tags

To read RFID tags:

1. Remove the MC319Z from AC power and ensure the LLRP icon is green.

✓ **NOTE** When connected to power, the mobile computer cannot read RFID tags.

2. Use an RFID reader application to enable tag reading. For a sample application, browse to the MC319Z **Application** directory and select **RFIDSample3Plus.exe**. See [Chapter 4, RFID Sample Application](#).
3. Aim the mobile computer at the tag, oriented horizontally or vertically depending on the tag orientation. The distance between the tag and the antenna is the approximate read range.
4. Press the trigger or tap the on-screen **Read** command within the application to interrogate all RFID tags within the radio frequency (RF) field of view and capture data from each new tag found. Release the trigger or tap the **Stop Read** command to stop interrogating tags.

Chapter 2 Updating the Mobile Computer

Introduction

This chapter describes how to update the device image and radio firmware.

Updating the Device Image

Windows Mobile contains an Image Update feature that updates all operating system components. Zebra distributes all updates as update packages on the Support Central Web Site <http://www.zebra.com/support>. These packages contain either partial or complete updates for the operating system.

To update an operating system component, copy the update package to the mobile computer using ActiveSync, AirBEAM, or MSP.

Downloading an Update Loader Package

1. Download the appropriate update loader package from the Zebra Support Central web site <http://www.zebra.com/support> to a host computer.
2. Locate the update loader package file on the host computer and un-compress the file into a separate directory:
 - **30XXw61RFIDSCxxxxx.zip** for updating via ActiveSync
 - **30XXw61RFIDABxxxxx.zip** for updating via AirBEAM

Updating Images via ActiveSync

To install an update loader package using ActiveSync:

1. Insert the mobile computer into the cradle and connect the cradle to AC power.
2. Connect the mobile computer to the host computer using ActiveSync.
3. In ActiveSync on the host computer, open **Explorer** for the mobile computer.
4. Copy the contents of **3190w65MenUL02270X\UpdateLoader** (the files only, not the folder) into the **\Storage Card** folder on the mobile computer.

5. On the mobile computer, navigate to the **\Storage Card** folder and tap the program **STARTUPDLDR.EXE**. The update takes approximately 10 minutes. Do not remove AC power during this time.
6. Copy **MCRFIDInstall.CAB** into the **\Storage Card** folder on the mobile computer.
7. On the mobile computer, navigate to the **\Storage Card** folder and tap **MCRFIDInstall.CAB**. The device reboots after the installation with RFID operational.

Updating Images via AirBEAM

Install the AirBEAM package files within **30XXw61RFIDABxxxxx.zip** in sequence:

1. **30XXw61MenUPRXXXXX.apf**
2. **30XXw61RFIDPkgXXXX.apf**

30XXw61RFIDPkgXXXX.apf executes silently and the mobile computer boots after installation, which takes approximately 7-10 seconds. Refer to the *MC3000 Integrator Guide* for more information on AirBEAM.

Updating the RFID Firmware

The **RFID_FLASH** utility, used to update the RFID radio firmware, is no longer provided. For related issues, contact Zebra support.

Chapter 3 MobileRFID Functionality

Introduction

MobileRFID is an RFID server application that runs in the background on the mobile computer. The MobileRFID icon appears in the system tray. This chapter includes information on using and configuring MobileRFID.








Figure 3-1 *MobileRFID Icon*

MobileRFID Icons

The MobileRFID icon indicates RFID radio status as described in [Table 3-1](#).

Table 3-1 *MobileRFID Icon Indicators*

Icon	Indication
	RFID running, radio on.
	RFID running, radio off.
	RFID stopped (radio not found/battery critical/stopped from user interface).
	RFID critical (radio muted, laser enabled).*
	RFID warning (Tx low power).*

***RFID critical and RFID warning due to transmit low power is not applicable to the MC319Z.**

MobileRFID Menu

If using RFID as the Windows default home screen, tap the RFID panel, then tap the **Settings** button.




Figure 3-2 MobileRFID Home Window and Settings Window

If not using RFID as the Windows default home screen, tap the MobileRFID icon in the system tray. A menu appears.



Figure 3-3 MobileRFID Icon Menu

Configure Region

Upon Startup

After upgrading the mobile computer, the following window appears on startup.




Figure 3-4 Country Not Set Window

1. Tap **ok**. When no country is selected, the **Region Configuration** window appears.



Figure 3-5 Region Configuration Window

2. Select the region of operation and communication standard as allowed by the regulatory standards of that country/region from the drop-down menus. The following warning message appears.



Figure 3-6 Region Selection Warning Message

3. Tap **Yes** to confirm. A window appears indicating success.



Figure 3-7 Region Selection Success Window

After Startup

If not done at startup, set the regulatory region as follows:

1. Invoke the MobileRFID menu, then tap **Configure Region**.
2. In the **Region Configuration** window, select a region from the **Region of Operation** drop-down menu.



Figure 3-8 Region Configuration Window

3. Tap **Yes** on the warning window that appears. A confirmation window appears upon successful completion.



Figure 3-9 Region Selection Success Window

4. Tap **ok**.

Configure RFID

RFID is in Server Mode by default. To configure RFID to operate in Client Mode:

1. Invoke the MobileRFID menu, then tap **Configure RFID**.



Figure 3-10 RFID Configuration Window

2. Select the **Client Mode** check box.
3. In the **LLRP Port** field, enter the port number on which the server waits for the RFID client to communicate. The default is 5084.
4. In the **Server IP** field, enter the server IP for the remote host to which RFID communicates as a client.
5. Tap **Apply**.
6. Tap **ok** to close the window.

Version Information

To view software version information for the RFID application, invoke the MobileRFID menu, then tap **About**.




Figure 3-11 *About MobileRFID Window*

This window displays the MobileRFID application version, radio library version, radio firmware version, and radio OEM data version.

- ✓ **NOTE** The version information in [Figure 3-11](#) may differ from the information on the actual mobile computer screen.

Run/Stop RFID

To stop RFID service tap **Stop** in MobileRFID menu. This frees the RFID radio.



Figure 3-12 RFID Stopped

To restart RFID, tap **Run** in MobileRFID menu.

Battery Configuration

The option to configure battery life/performance is available from version 3.2.6004 of the MC319Z software.

The configure performance option is used to manage battery life of the MC319Z. There are five different pre-configured settings to balance between read-performance and battery life. Battery life will be maximum when the slider bar is kept to the left-most. The device will perform at maximum performance efficiency when the slider bar is kept to the right-most. By default, the slider bar is set at the center.

All settings made using this option can be overwritten using RFID3 API configuration settings.




Figure 3-13 Battery Performance Configuration

Chapter 4 RFID Sample Application

Introduction

The RFID Application CS_RFID3Sample6.exe provides an overview of how the application works and assists application developers in developing custom applications.

The mobile computer can read, write, lock, kill, and program Gen2 tags. Each tag contains the EPC number (64 or 96 bits), CRC, and kill code. The mobile computer can also collect data by decoding in-range EPC Gen2 RFID tags.

Initiating the read command within the sample application causes the mobile computer to interrogate all RFID tags within the radio frequency (RF) field of view. The reader captures data from each new tag and adds it to the list box in the **EPC ID** window. Select **Stop Read** to stop interrogating tags.

Launching the RFID Sample Application

Select **RFID Demo** in the **Start** menu to start the RFID sample application.



Figure 4-1 RFID Demo Icon




Figure 4-2 RFID Sample Application Window

In the sample application window:

- Tap the **Start Reading** button to initiate the tag read. Tap **Stop Reading** to terminate tag reading.
- Use the **Mem Bank** drop-down to select a tag memory bank to read. The default memory bank is EPC (**None**). Other options are **TID**, **Reserved**, and **User**.

Connection

Tap **Connection** to display the reader IP and port number.



Figure 4-3 *Connection Window*

Select **Disconnect** to disconnect the reader.

Capabilities

Select **Menu > Capabilities** to view the capabilities of the connected reader.



Capability	Value
Reader ID	381506D0B09...
Firmware Version	1.02.04
Model Name	3190
No. of Antennas	2
No. of GPI	1
No. of GPIO	0
Max Ops in Access Seque...	8
Max No. Of Pre-Filters	3
Country Code	840
Communication Standard	US_FCC_PART_15
UTC Clock	True
Block Erase	True

Figure 4-4 *Capabilities Window*

Configuration Menu Options

The Configuration menu includes the following options:

- Tag Storage Settings
- Antenna
- RF Mode
- Singulation
- Power On/Off Radio
- Reset to Factory Defaults

Tag Storage Settings

Select **Menu > Config > Tag Storage Settings** to view/configure tag storage settings.



The screenshot shows a mobile application window titled "Tag Storage Settings". The window has a black header bar with the title and several status icons (Wi-Fi, Bluetooth, speaker, battery, and time 2:42). Below the header, there are three text input fields with the following labels and values:

Field Label	Value
Maximum Tag Count	64
Max Tag ID Length (Bytes)	12
Max Size of Memory Bank (Bytes)	64

At the bottom right of the input area, there is a pink "Apply" button. The bottom of the screen features a green navigation bar with three circular icons: a Windows logo, a keyboard icon, and an "OK" button.

Figure 4-5 *Tag Storage Settings Window*

This window includes the following fields:

- **Maximum Tag Count** - The maximum number of tags to store in the DLL.
- **Max Tag ID Length** - The maximum tag length.
- **Max Size of Memory Bank** - Storage to allocate for the memory bank's data.
- **Apply** - Select to apply the configuration changes.

Antenna

Select **Menu > Config > Antenna** to view/configure the antenna.

Antenna Config 7:27

Antenna ID: 1

Receive Sensitivity (dB): 0

Transmit Power (dBm): 2700

Hop Table Index: 1

915750, 915250, 903250, 926750,
926250, 904250, 927250, 920250

Apply

Figure 4-6 *Antenna Configuration Window*

This window includes the following fields:

- **Antenna ID** - Selecting an antenna ID updates the configuration values in the other fields.
- **Receive Sensitivity (dB)** - Lists the reader-supported values for the selected antenna.
- **Transmit Power (dBm)** - Lists the reader-supported values for the selected antenna.
- **Hop Table Index** - Updates the Hop Frequency list with its corresponding frequencies.
- **Apply** - Select to apply the configuration changes.

RF Mode

Select **Menu > Config > RF Mode** to view/configure the RF mode for each antenna.

Parameter	Value
Mode Identifier	18
DR	DR_64_3
Bdr	62500
M	MV 4

Figure 4-7 RF Mode Window

This window includes the following fields:

- **Antenna ID** - Selecting an antenna ID updates the configuration values in the other fields.
- **Tari Value** - TARI specified in nsec.
- **RF Mode Table** - RF mode table configured for the current antenna.
- **Apply** - Select to apply the configuration changes.

Singulation

Select **Menu > Config > Singulation** to view/configure the singulation control settings for each antenna.

The screenshot shows a mobile application window titled "Singulation". At the top right, there are icons for signal strength, volume, and battery, along with the time "7:29". The main area contains the following settings:

- Antenna ID: 1 (dropdown menu)
- Session: S0 (dropdown menu)
- Tag Population: 100 (text input)
- Tag Transit Time: 0 (text input)
- State Aware: (checkbox)
- Inventory State: STATE A (dropdown menu)
- SL Flag: DEASSERTED (dropdown menu)

An "Apply" button is located at the bottom right of the settings area. The bottom of the screen features a green bar with three circular icons: a Windows logo, a keyboard icon, and an "OK" button.

Figure 4-8 Singulation Control Settings Window

This window includes the following fields:

- **Antenna ID** - Selecting an antenna ID updates the configuration values in the other fields.
- **Session** - The session number for the inventory operation.
- **Tag Population** - The approximate tag population in the RF field of the antenna.
- **Tag Transit Time** - The time in milliseconds that the tag typically remains in the RF field of the antenna.
- **State Aware** - Indicates if the antenna performs state aware or state unaware singulation.
- **Inventory State** - Select a tag of state A or B. Valid only for State Aware singulation
- **SL Flag** - Valid only for State Aware singulation
- **Apply** - Select to apply the configuration changes.

Power On/Off Radio

Select Menu > Config > Power On/Off Radio to change the power settings of the RFID radio.



Figure 4-9 Radio Power Settings Menu

Reset to Factory Default

Select Menu > Config > Reset to Factory Default to restore the default reader configuration.

Operations Menu Options

The **Operations** menu includes the following options:

- Antenna Info
- Filter
- Access
- Triggers

Antenna Info

Select **Menu > Operations > Antenna Info** to view/configure the list of antennas that can be used for inventory/access operations.




Figure 4-10 *Antenna Info Window*

Filter

Select **Menu > Operations > Filter** to view/configure the following filters:

- Pre-Filter
- Post-Filter
- Access-Filter

Pre-Filter

Select **Menu > Operations > Filter > Pre-Filter** to view/configure pre-filters.

The screenshot shows the 'PreFilter' window with the following configuration:

- Antenna ID:** 1 (dropdown menu), Use Filter 1
- Memory Bank:** EPC (dropdown menu), **Offset:** 32 (text input)
- Tag Pattern:** aabbccdd (text input)
- Filter Action:** STATE AWARE (dropdown menu)
- Action:** INV A NOT INV B (dropdown menu), **Target:** SO (dropdown menu)

At the bottom, there are two tabs labeled 'Filter 1' and 'Filter 2', an 'Apply' button, and a Windows-style taskbar with 'Start', 'Keyboard', and 'OK' icons.

Figure 4-11 *PreFilter Window*

This window includes the following fields:

- **Antenna ID** - Selecting an antenna ID updates the configuration values in the other fields.
- **Memory Bank** - Memory bank on which the filter is applied.
- **Offset** - The first (msb) bit location of the specified memory bank against which to compare the tag mask.
- **Tag Pattern** - The pattern against which to compare the specified memory bank.
- **Filter Action** - Select the required filter action. For more information, refer to the Gen2 specification available at <http://www.epcglobalinc.org/standards/>.

Post-Filter

Select **Menu > Operations > Filter > Post-Filter** to view/configure post-filters.

The screenshot shows the 'PostFilter' configuration window. The title bar includes the text 'PostFilter' and the time '7:33'. The main area contains the following fields:

- Memory Bank:** A dropdown menu with 'USER' selected.
- Offset:** A text input field containing the number '2'.
- Tag Pattern:** A text input field containing 'aabb'.
- Tag Mask:** A text input field containing 'ffff'.
- Tag Pattern A / Tag Pattern B:** A section with two tabs. 'Tag Pattern B' is selected and highlighted in pink.
- Match Pattern:** A dropdown menu with 'A AND B' selected.
- Use Filter:** A checkbox that is checked.
- Apply:** A button to apply the settings.

At the bottom of the screen are three circular icons: a Windows logo, a keyboard icon, and an 'OK' button.

Figure 4-12 *PostFilter Window*

This window includes the following fields:

- **Memory Bank** - Memory bank on which the filter is applied.
- **Offset** - The first (msb) bit location of the specified memory bank against which to compare the tag mask.
- **Tag Pattern** - The pattern against which to compare the specified memory bank.
- **Tag Mask** - The bit mask to facilitate bit wise filtering.
- **Match Pattern** - Select the tag pattern to match (A, B, both, or neither).

Access-Filter

Select **Menu > Operations > Filter > Access-Filter** to view/configure the access-filters.

The screenshot shows the 'AccessFilter' configuration window. The title bar includes the text 'AccessFilter' and the time '7:39'. The main area contains the following fields and controls:

- Memory Bank: A dropdown menu with 'EPC' selected.
- Offset: A text input field containing '32'.
- Tag Pattern: A text input field containing '11223344'.
- Tag Mask: A text input field containing 'ffffff'.
- Tag Pattern A and Tag Pattern B: Two tabs, with 'Tag Pattern A' currently selected.
- Match Pattern: A dropdown menu with 'A' selected.
- Use Filter: A checked checkbox.
- Apply: A button to apply the settings.

At the bottom of the window, there are three circular icons: a Windows logo, a keyboard icon, and an 'OK' button.

Figure 4-13 *AccessFilter Window*

See [Post-Filter on page 4-12](#) for field descriptions.

Access

Select **Menu > Operations > Access** to perform the following access operations.




Figure 4-14 Access Menu

The **Access** menu includes the following options:

- Read
- Write
- Lock
- Kill
- Block Write
- Block Erase

To perform an access option on a single tag, right-click the tag in the list of read tags on the main window to invoke the tag's context menu.




Figure 4-15 Tag Context Menu

Access Operation Windows

The access operation windows include the following fields. Set options as required in the various parameter windows. Not all windows include all options.

- **Tag ID** - The name of the selected tag.
- **Password** - Set a password before performing any access operation (except Kill).
- **Memory Bank** - Select the memory bank (Reserved, EPC, TID, User)
- **Offset** - Offset of the first word to read from the selected memory bank.
- **Length** - Tag/data length.
- **Write Data** - The data to write to the selected tag (Write window only).
- **Lock Privilege** - Access options for the selected tag (Write window only):
 - **None** - The can not change the lock privilege of the particular memory bank.
 - **Read_Write** - The user can read and write to the tag.
 - **Perma_Lock** - Permanent lock.
 - **Perma_Unlock** - Permanent unlock.
 - **Unlock** - The user can unlock the tag for writing.




Figure 4-16 Read Access Operation Window



Figure 4-17 Write / Block-Write Access Operation Window



Figure 4-18 Lock Access Operation Window



Figure 4-19 Kill Access Operation Window




Figure 4-20 Block Erase Access Operation Window

Triggers

Select **Menu > Operations > Trigger** to view/configure the following triggers:

- Start Trigger
- Stop Trigger
- Report Trigger

Start Trigger

Trigger

Trigger Type: Periodic

Start Date: Mar /31/11 07:20:24 PM

Period (ms): 1

Start Trigger | Stop Trigger | Report Trigger

Tag Report Trigger: 0 | Apply

Windows | Keyboard | OK

7:43

Figure 4-21 Start Trigger - Periodic Window

Trigger

Trigger Type: GPI

Event: 1

High To Low

Low To High

Start Trigger | Stop Trigger | Report Trigger

Tag Report Trigger: 0 | Apply

Windows | Keyboard | OK

1:14

Figure 4-22 Start Trigger - GPI Window



Figure 4-23 Start Trigger - Handheld Trigger Window

Stop Trigger



Figure 4-24 Stop Trigger - Periodic Window

The screenshot shows a mobile application window titled "Trigger". At the top right, there are icons for signal strength, speaker, battery, and the time 12:48. The main content area contains the following fields:

- Trigger Type: A dropdown menu showing "GPI with TimeoL".
- Port: A dropdown menu showing "1".
- Time Out: A text input field containing "2000".
- Event: Two radio buttons, "High To Low" (checked) and "Low To High" (unchecked).

Below the main content area is a row of four buttons: "Start Trigger", "Stop Trigger", "Report Trigger", and an empty button. At the bottom of the main content area is a "Tag Report Trigger" field with the value "0" and an "Apply" button. The bottom of the screen features a green bar with three circular icons: a Windows logo, a keyboard icon, and an "OK" button.

Figure 4-25 Stop Trigger - GPI with Timeout Window

The screenshot shows a mobile application window titled "Trigger". At the top right, there are icons for signal strength, speaker, battery, and the time 12:48. The main content area contains the following fields:

- Trigger Type: A dropdown menu showing "Tag Observator".
- Tag Observation: A text input field containing "5".
- Time: A text input field containing "1000".

Below the main content area is a row of four buttons: "Start Trigger", "Stop Trigger", "Report Trigger", and an empty button. At the bottom of the main content area is a "Tag Report Trigger" field with the value "0" and an "Apply" button. The bottom of the screen features a green bar with three circular icons: a Windows logo, a keyboard icon, and an "OK" button.

Figure 4-26 Stop Trigger - Tag Observation with Timeout Window



Figure 4-27 Stop Trigger - N Attempts with Timeout Window




Figure 4-28 Stop Trigger - Handheld Trigger with Timeout Window

Report Trigger

Trigger

New Tag Moderated 500

Tag Invisible Moderated 500

Tag back to visibility Moderated 500

Start Trigger Stop Trigger Report Trigger

Tag Report Trigger 0 Apply

Windows Keyboard OK

Figure 4-29 Report Trigger Window

Management Menu Options

Management options are not applicable for handheld readers.

Help Menu

Select **Menu > Help** to display the version information. The version numbers displayed in this window are examples. Actual version numbers are based on the versions of the files on the device.




Figure 4-30 Help Window

Exit

Select **Menu > Exit** to exit the RFID sample application.

Chapter 5 Tag Locator

Introduction

Use Tag Locator to detect the location of a tag. By providing the TagID of an item, this application can find the relative position of the tag with respect to the mobile computer. Move the mobile computer back and forth to obtain the location of the tag as indicated by the beep frequency and a vertical progress bar showing the relative position of the tag.

The Tag Locator application requires the following components/DLLs on the device:

- RFIDAPI32.dll (Version 5.1.15 or higher)
- Symbol.RFID3.Device.dll (Assembly version 1.1.0.1, File version 1.1.0.7 or higher)
- Symbol.Audio.dll
- Symbol.dll
- Symbol.Notification.dll
- Symbol.StandardForms.dll

Using Tag Locator

To use the Tag Locator application:

1. Tap **TagLocator** in the **Application** folder on the mobile computer to open the Tag Locator application.



Figure 5-1 *Tag Locator*

2. Enter the tag ID in one of three ways:

- Type the tag ID in the **TagID** text box, then select **Locate** or press and hold the trigger.
- Perform a search operation by selecting the **Search Tags** button or by pressing and holding the trigger.
- Select the **Import Tags** button to import a list of saved tags from a .csv file. See [Locating Tags Using a .csv File on page 5-3](#).

Locating Tags Using a .csv File

1. Select the **Import Tags** button to import a list of saved tags from a .csv file. The following window appears.




Figure 5-2 Opening a .csv File

2. Select the desired .csv file to import the tags to the list.




Figure 5-3 Tag List

3. Select a tag from the list to search.

4. Select the **Locate** button or press and hold the trigger. Move the mobile computer in all directions to get the relative position of the tag, indicated by a beep, the vertical progress bar, or both.




Figure 5-4 Tag Search

Use the **Options** menu to turn the beeper on and off and to display data in ASCII or hexadecimal format.




Figure 5-5 Options Menu

Chapter 6 Troubleshooting

Introduction

Table 6-1 on page 6-1 provides troubleshooting information.

Troubleshooting

Table 6-1 *Troubleshooting*

Problem	Possible Causes	Possible Solutions
Mobile computer does not turn on.	Lithium-ion battery not charged.	Charge or replace the lithium-ion battery.
	Lithium-ion battery not installed properly.	Ensure battery is installed properly. Refer to the <i>MC3000 Mobile Computer Integrator Guide</i> .
	System crash.	Perform a warm boot. If the RFID reader still does not turn on, perform a cold boot. Refer to the <i>MC3000 Mobile Computer Integrator Guide</i> .
Rechargeable lithium-ion battery did not charge.	Battery failed.	Replace battery. If the mobile computer still does not operate, try a warm boot, then a cold boot. Refer to the <i>MC3000 Mobile Computer Integrator Guide</i> .
	Mobile computer removed from cradle while battery was charging.	Insert mobile computer in cradle and begin charging. The lithium-ion battery requires less than four hours to recharge fully.
Mobile computer turns off without proper warning messages during heavy use.	Due to component tolerances, this can occur when using battery part number 55-060112-xx.	Use battery 55-002152-xx (p/n 82-127909-xx).
No sound.	Volume setting is low or turned off.	Increase the volume setting.

Table 6-1 *Troubleshooting (Continued)*

Problem	Possible Causes	Possible Solutions
Tapping the window buttons or icons does not activate the corresponding feature.	LCD screen not aligned correctly.	Re-calibrate the screen.
	Battery is not inserted properly.	Insert the battery properly. Refer to the <i>MC3000 Mobile Computer Integrator Guide</i> .
A message appears stating that the mobile computer memory is full.	Too many files stored on the mobile computer.	Delete unused memos and records. Save these records on the host computer.
	Too many applications installed on the mobile computer.	If additional applications have been installed on the RFID reader, remove them to recover memory. Tap Start > Settings > System tab > Remove Programs icon.
Reader is not reading tags.	The tag is out of its read range. Tags are damaged. Tags are not EPCgen2. Read application is not loaded.	Move the tag into the read range. See Reading Tags on page 1-5 . Use tags of good quality. Use EPCgen2 tags. Verify that the unit is loaded with a read application.
Reader is not reading tags and the LLRP icon is red.	The battery is cold or degraded.	Recharge or replace the battery. If the problem still exists, exit and restart LLRP.



NOTE If problems still occur, contact the distributor or call the local contact. See [page xi](#) for contact information.

Appendix A Technical Specifications

Technical Specifications

The following tables summarize the RFID reader intended operating environment and technical hardware specifications.

Table A-1 *Technical Specifications*

Item	MC319Z RFID
Physical and Environmental Characteristics	
Dimensions	9.1 in. L x 3.6 in. W x 7.6 in. H 23.1 cm L x 9.1 cm H x 19.3 cm H
Weight	23 oz. / 650 g (includes battery, RFID, scanner, and radio)
Keypad	48 key Terminal Emulation (5250, 3270, VT)
Display	3 in. 320 x 320 pixel color
Battery	Extended capacity (2X) battery pack
Performance Characteristics	
CPU	Intel® XScale® Bulverde PXA270 processor at 624MHz
Operating System	Microsoft Windows Mobile 6.5
Memory (RAM/ROM)	256 MB RAM/1 GB Flash
Application Development	SMDKs available through the Support Web Site
Data Capture Options	Laser engine reads 1D symbologies with intuitive laser aiming. RFID reader reads Gen2 tags.

Table A-1 *Technical Specifications (Continued)*

Item	MC319Z RFID		
Laser Decode Capability	Code 39 Codabar Interleaved 2 of 5 MSI UPC/EAN supplementals Webcode GS1 DataBar Expanded Composite Code Macro PDF417 Data Matrix Australian 4-State Dutch Kix MicroQR	Code 128 Code 11 EAN-8 UPCA Coupon Code GS1 DataBar EAN-128 PDF417 MSI Plessey US Planet Canadian 4-State Aztec	Code 93 Discrete 2 of 5 EAN-13 UPCE Trioptic 39 GS1 DataBar Limited TLC39 Micro PDF417 Maxi Code UK 4-State Japanese 4-State USPS 4-State(US4CB)
User Environment			
Operating Temperature	-4°F to 122°F (-20°C to 50°C)		
Battery Charging Temperature	32° to 104° F (0° to 40° C) ambient temperature range		
Storage Temperature	-25°F to 160°F (-40°C to 70°C)		
Humidity	0% to 95% non condensing		
Drop Specification	Multiple 6 ft. (1.8m) drops to concrete across operating temperature range		
Tumble	2,000 one-meter tumbles at room temperature (4,000 hits)		
Environmental Sealing	IP64		
ESD	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge		
RFID			
Standards Supported	EPC Generation 2 UHF		
Nominal read range ¹	10 ft./3.04 m with the RFX6000 4x4 tag optimally oriented.		
Field	Half read range beam width: +/- 80 degrees (with tags optimally oriented).		
Antenna	Integrated, circularly polarized, 1.5 dB effective linear gain per axis (nominal); Antenna port for future support of optional external antenna.		
Frequency Range	902-928 MHz		
Output power	1W conducted (1.4W EIRP with integrated antenna)		

Table A-1 *Technical Specifications (Continued)*

Item	MC319Z RFID
Wireless Data Communications	
WLAN	802.11a/b/g
Output Power	100mW U.S. and International
Data Rate	802.11a: 54Mb per second 802.11b: 11Mb per second 802.11g: 54Mb per second
Antenna	Internal
Frequency Range:	802.11a: 5 GHz; country-dependent 802.11b: 2.4 GHz; country-dependent 802.11g: 2.4 GHz; country-dependent
Bluetooth	Bluetooth® Version 1.2 with BTEplorer™ (manager) included
Peripherals and Accessories	
Cradles	Single-slot available
Printers	Supports extensive line of Symbol approved printers, cables and accessories
Charger	4-Slot universal battery charger
Other Accessories	Cable Adapter Module; Magnetic Stripe Reader; Modem; Full set of holsters In accordance with the SymbolPlus partner program

Appendix B RFID APIs

RFID APIs are available in C and NET. For information on supported RFID APIs, refer to the *Enterprise Mobility Developer Kit* (EMDK), available at <http://www.zebra.com/support>.

For C, refer to the EMDK for C v2.1 or later. For .Net, refer to the EMDK for .NET v2.2 or later.

Index

A

activesync 2-1
airbeam 2-2
antenna 1-2, 1-3
APIs B-1

B

battery 6-1, A-1
battery charging temperature A-2

C

charge LED indicator 1-4
configuration ix
configuring MobileRFID 3-7
 region 3-4
connection
 ports 1-4
 sample application 4-3
conventions
 notational x
CPU A-1

D

data capture ix, A-1
demo 4-1
 connection 4-3
 launching 4-2
dimensions A-1
display A-1
drop specification A-2

F

firmware update 2-2

H

humidity A-2

I

icons
 MobileRFID 3-2
image update 2-1
 activesync 2-1
 airbeam 2-2
 update loader 2-1

K

keypad ix, A-1

L

LEDs 1-5
locating tags 5-1

M

memory A-1
MobileRFID 3-1
 client mode 3-7
 configuring 3-7
 configuring region 3-4
 icons 3-2
 menu 3-3
 server mode 3-7
 starting 3-9

stopping 3-9
 version information 3-8

O

operating system ix, A-1
 operating temperature A-2

P

ports 1-4

R

radio 1-2
 reading tags 1-5
 problems 6-2
 region
 configuring 3-4
 RFID APIs B-1
 RFID components 1-2
 antennas 1-2
 radio 1-2
 tags 1-2
 RFID firmware update 2-2
 RFID overview 1-1

S

sample application 4-1
 connection 4-3
 launching 4-2
 scan buttons 1-4
 scan LED indicators 1-4
 service informationxi
 specifications A-1
 starting RFID 3-9
 stopping RFID 3-9
 storage temperature A-2
 supportxi

T

tags 1-2
 locating 5-1
 problems reading 6-2
 reading 1-5
 technical specifications A-1
 temperature A-2
 troubleshooting 6-1

U

updating device 2-1

activesync 2-1
 airbeam 2-2
 firmware 2-2
 RFID firmware 2-2
 update loader 2-1

V

volume 6-1

W

weight A-1
 Windows Mobile 6.5 ix



Zebra Technologies Corporation
Lincolnshire, IL U.S.A.
<http://www.zebra.com>

Zebra and the Zebra head graphic are registered trademarks of ZIH Corp. The Symbol logo is a registered trademark of Symbol Technologies, Inc., a Zebra Technologies company.

© 2015 Symbol Technologies, Inc.



72E-146158-03 - Revision A - March 2015