

KDC200 Laser Barcode Data Collector

A New Wave in Auto-ID

The KDC200 enables diverse mobile Auto-Identification applications for collecting and storing barcode data.

A built in display eliminates blind erroneous data collections and enables interactive data collection processes.

An easy-to-replace rechargeable battery that can recharge from any USB port allows more than 5,000,000 barcode scans. With 4MB of on-board memory that stores over 100,000 product records, memory shortages are also no longer a problem.

All KDC® products come with FREE KTSync® software (includes keyboard wedging, application generation, DB look up and inventory management features) and FREE SDK (includes technical support from our top engineers and development staff).



BlackBerry



Windows

Made for



iPod



iPhone



iPad



ADVANCED FEATURES

- Ultra Compact & Lightweight
- Class2 Bluetooth® with HID/SPP/ MFi(200i model only) Profiles
- Bright 1" OLED Display
- Rechargeable Li-Poly Battery
- Stores 100,000+ Product Records
- KTSync® with Keyboard Wedging, Application Generation, DB Look up and Inventory Management features.

- Transportation
- Logistics
- Healthcare Services
- Field Services
- Distribution & Retail
- Property Management



KDC200 Specifications

Hardware Specifications

Physical Characteristics

Size : 1.37" x 2.44" x 0.59" (35mmx62mmx15mm)

Weight : 1.2 oz. (34 grams)

Electrical Characteristics

Battery : Lithium-Polymer (3.7V DC, 190mAh)

Charging : Via USB connector

Typical Operating Current : 120mA@3.3V

Scanning Performance

Scan Rate : 100 scans/sec

User Environment

Drop Spec : 4 feet (1.22m) with Rubber Case

Operating : 32°F (0°C) ~ 113°F (45°C)

Storage : -4°F (-20°C) ~ 113°F (45°C)

Humidity : 5% ~ 85% (noncondensing)

Interfaces

Bluetooth® V2.1+EDR, Class 2, HID/SPP/MFi(i model only)

USB to Serial (Ultra mini USB port)

Functionality

Memory Flash ROM : 256KB Program, 4MB User Data

Memory RAM : 64KB

Microprocessor : ARM7, 32 bits

Real-time Clock : Quartz RTC for timestamp

Symbologies

EAN, UPC, Code 39, Code 93, Code 128, Codabar, Interleaved 2 of 5, GS1-128, Code 3 of 5

Wedging & Synchronization

- Store to a file or transfer to the application
- Keyboard wedge function
- Add-on prefixes and suffixes
- Barcode option selection

Application Generation

- SDK for PC, Pad and Smartphone application
- Application generation tool
- Database lookup feature
- Inventory management feature

Regulatory Conformance

Laser Safety - IEC Class I, CDRH Class II

EMC - CE, FCC, MIC, TELEC, SRRC

Models

KDC200 – USB & Bluetooth® HID/SPP

KDC200i – USB & Bluetooth® HID/SPP/MFi

Package Contents

- 1 Data Collector with rechargeable battery
- 1 USB cable, 1 Lanyard, 1 Software CD,
- 1 Protective Boot, optional Finger Trigger Glove



For more information, contact us at:

KoamTac, Inc.
116 Village Boulevard, Suite 200 Princeton,
NJ 08540, USA

Tel +1-609-734-4335
Fax +1-609-228-4373
E-mail info@koamtac.com
www.koamtac.com

